

READY 
TO RACE

EN



KTM 125 DUKE

TECHNICAL INFORMATION





TECHNICAL DATA

2024-26 KTM 125 DUKE

ENGINE (LIQUID COOLED)

ENGINE TYPE	1 cylinder, 4 stroke (EURO5+)
DISPLACEMENT	124.99 cc
BORE/STROKE	58 / 47.3 mm
POWER	15 PS @ 10,000 rpm
TORQUE	11,5 Nm @ 7,750 rpm
COMPRESSION RATIO	12.6:1
TRANSMISSION	6 gears
FUEL SYSTEM	Bosch EFI (electronic throttle body 33 mm)
CONTROL	4 valves / SOHC
COOLING	Liquid cooled with water
CLUTCH	PASC slipper clutch, mechanically operated
ENGINE MANAGEMENT	Bosch EMS with RBW
FUEL CONSUMPTION	2.4 L / 100 km
CO2 EMISSIONS	57 g / km

CHASSIS

FRAME	Steel trellis frame, powder coated
SUBFRAME	Bolt on casted aluminium frame, powder coated
HANDLEBAR	Aluminium, tapered
FRONT SUSPENSION	WP APEX USD 43 mm (non-adjustable)
REAR SUSPENSION	WP APEX shock absorber
SUSPENSION TRAVEL FRONT/REAR	150/150 mm
FRONT BRAKE	Four piston, radially mounted caliper, brake disc Ø 320 mm
REAR BRAKE	Single piston, floating caliper, brake disc Ø 240 mm
FRONT/REAR RIMS	3"/R17 - 4"/R17
FRONT/REAR TIRES	110/70 R17 M/C 54W TL - 150/60 R17 M/C 66W TL
WHEEL BASE	1,357 mm
SEAT HEIGHT	800 mm

KEY FEATURES

- 5" Color TFT dashboard
- Overcoated graphics
- LED lights